



		Class	Weight
1	Cover according to standard EN124 (☒)	A35 (3,5 t) □	13 kg
		B125 (12,5 t) □	45 kg
		C250 (25 t) □	55 kg
		D400 (40 t) □	90 kg
2	Maintenance shaft (☒)	800...1000 □	31 kg
		1000...1250 □	33 kg
		1250...1500 □	42 kg
		1500...1750 □	52 kg
		1750...2000 □	62 kg
		2000...2250 □	71 kg
		2250...2500 □	80 kg
3	Ladder		
4	Automatic closure		
5	Coalescing modules		
6	Sludge trap	6000 l	
7	Oil storage capacity	820 l	
8	Effective capacity	7200 l	
9	Oil level alarm sensor (☒)	□	
	Nominal flow rate	30 l/s	
	Total capacity	13200 l	
	Weight excluding manhole shaft/lid	1420 kg	

Product Snigo	Name Oil/water separator SEPKO 30/6000	Scale 1:50
Design by M.Skuzinskas	Checked by E.Mozuraitis	Approved by E.Kuodis
 UAB ENEKA Vandziogalos g. 94 LT-47467 Kaunas, Lithuania tel. +37037377441, faks. +37037377907 www.eneka.lt, info@eneka.lt		Drawing type Customer drawing Drawing no. - Date 8/31/2016
Construction site -		Lang. Sheet en 1